

MICR MX-3 Series Encoder

The process of encoding exception items at the point-of-entry enables production oriented work groups such as proof and item processing departments to operate at peak efficiency. Items that cannot be posted as part of the normal financial presentment such as suspect items, signature verification, large dollar items, non-sufficient funds (NSF), and missing MICR data can be encoded with the *MX-3* to fully qualify the exception item.



STANDARD PROGRAM FEATURES

The *MX-3* is completely field programmable through the keyboard.

- On-board advanced diagnostics and test mode
- 8 programmable functions
- Each function key can be programmed to scroll up to 100 different fields CDV/CDG (each field)
- Auto Incrementing serial numbers
- Auto-repeat encoding
- Floating On-Us feature
- Field "look-up" feature
- Single pass, full field encoding
- Dog-ear detection
- Ribbon out detection
- Robust keyboard design
- Self calibrating Sensors

Nationwide Sales and Customer Support

The full line of Maverick Products are sold and serviced nationwide by a highly trained and professional network of Maverick Distributors. For more information about the MICR *MX-3* and other products please contact your local authorized Maverick Distributor or the Maverick corporate office.

The *MX-3* Exception Item Encoder provides full keyboard programmability for maximum flexibility. Eliminate cost and lost time associated with programming changes that can only be done at the factory. With state-of-the-art circuitry and a stout mechanical design, the *MX-3* eliminates downtime. The *MX-3* meets or exceeds the rigid ANSI MICR specification for MICR encoding and features a ribbon cartridge that is simple to change with absolutely no mess. This unit is lightweight, compact and is a perfect fit for a small work center.

ENCODER SPECIFICATIONS

Speed:	45 dpm
Length:	13.25 inches (33.7 cm)
Width:	8.0 inches (20.32 cm)
Height:	3.5 inches (8.89 cm)
Weight:	4.25 pounds (1.93 kg)
Display:	20 character, 2-line alphanumeric Backlit LCD
Ribbon:	Average yield of 25,000 - 30,000 characters
Power:	120 VAC, wall mount transformer (or) 100-240 VAC, in-line desktop
Memory:	Non-Volatile, FLASH ROM
Encode Capability:	65 character/full field
Font:	E13B (other fonts available)
Options:	Coming Soon

Your authorized Maverick Distributor is:

