



Flexible. Compatible. Scalable.
Technology you can bank on.

Maximize client satisfaction and branch productivity with the next generation of secure, customer-centric branch transformation platforms from Nautilus Hyosung. The **MX8800** streamlines branch transactions and delivers quick and secure autonomously or with the assistance of branch staff.

EXPERIENCE THE POWER OF CHANGE.

MAXIMIZE PRODUCTIVITY

- The **MX8800** automates many routine teller transactions seamlessly and supports a variety of options for supporting the customer in person or via remote video conference. The result? The ability for branches to handle more transactions with fewer resources.

BUILD TRUST

- The **MX8800's** many security features protect both consumer and institutional data enabling the ability to develop long-term, trusted, client relationships.

EXCEED CLIENT EXPECTATIONS

- Today's customers demand safe, secure, and efficient money-management solutions. The **MX8800** increases client satisfaction levels by supporting self-service and assisted transactions from a single terminal.

CUSTOMIZE YOUR SOLUTION

- Choose from a wide variety of configuration and integration options, standard hardware features, and personal engagement tools to meet customers' unique needs while optimizing branch time and resources.

EMPOWER BRANCH EMPLOYEES

- Serve more customers in new ways by eliminating manual processes. The **MX8800** frees staff to focus on identifying and promoting bank products that can help customers achieve their financial goals.

System Control

- Microsoft® Windows 7®
- CEN/X FS 3.10 or later

Customer Interface

- Upper 24" Wide TFT LCD
- Lower 15" TFT LCD (touch screen)

Operator Panel

- 15" TFT LCD (touch screen) at the rear of the machine.

Communication

- TCP/IP

Cash Dispensing

- Up to five 3,000 note cassettes
- Coin Dispenser (optional)

Card Reader / Input Type

- EMV Dip track 1,2
- EMV Motorized Track 1,2
- Contactless card reader (optional)
- Anti-skimming (optional)
- 15" Lower touch screen
- PCI compliant EPP, T-DES, DES, RSA

Cash Handling

- Cash recycling technology
- Bulk cash insertion
- High capacity dispense capability
- 5 configurable cassettes for deposits/dispense
- Insertion or dispense
- Cash and Check depository; single insertion mixed media depository
- Reject and retract capability
- Bunch Check Insertion

Printers

- 3.1" graphic thermal receipt printer

Power Supply

- AC 110-240 V, 50-60 Hz
- Backup battery (Reserving last transaction and safe shutdown)

Security

- UL291 Level-1
- Optional camera
- Keypad shield
- Secure lower LCD

Additional Features

- 2D Barcode reader
- Audio jack for ADA
- ID scanner (optional)
- Two way audio and video capable (optional)
- Handset (optional)

Operating Environment

- Temperature: 0°C~ 40°C (32°F – 104°F)
- Humidity: 20% ~ 85%

Dimensions

- Height: 42.2" (1,072mm)
Total: 55.2" (1,401mm)
- Width: 34.6" (890mm)
- Depth: 44.5" (1,130mm)
Total: 55.8" (1,418mm)
- Weight: 1,886lbs. (850kg)

**Subject to note quality and other variables*



Contact your account manager for more information.
 Tipton Systems St. Louis 800-899-2997
 Tipton Systems Kansas City 800-844-5312